

Enriching lives through innovation

SAFETY DATA SHEET Natural Red Iron Oxide

1. Identification

Product identifier

Product name

Natural Red Iron Oxide

Product number

521,NO1085,NO1283

Recommended use of the chemical and restrictions on use

Application

Industrial color

Details of the supplier of the safety data sheet

Supplier

Huntsman Pigments Americas LLC

P.O. Box 4980

The Woodlands, TX 77387

+1 301 210 3400 / +1 323 269 7311

MSDS@huntsman.com

Emergency telephone number

Emergency telephone

CHEMTREC: (800) 424-9300 (Contract No: 191118)

2. Hazard(s) Identification

Classification of the substance or mixture

Physical hazards

Not Classified

Health hazards

Eye Irrit. 2A - H319 Carc. 1A - H350 STOT RE 2 - H373

Environmental hazards

Not Classified

Label elements

Pictogram





Signal word

Danger

Hazard statements

H319 Causes serious eye irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapor/spray.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 If exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

Contains

CRYSTALLINE SILICA

3. Composition/Information on Ingredients

Mixtures

C.I. PIGMENT RED 101

> 80%

CAS number: 1309-37-1

REACH registration number: Proprietary

Classification

Not Classified

CRYSTALLINE SILICA

< 9%

CAS number: 14808-60-7

Classification

Carc. 1A - H350 STOT RE 2 - H373

ALUMINUM OXIDE

1-5%

CAS number: 1344-28-1

Classification

Not Classified

CALCIUM OXIDE

< 1%

CAS number: 1305-78-8

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318

MAGNESIUM OXIDE

1-5%

CAS number: 1309-48-4

Classification

Not Classified

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation If exposed to excessive levels of dust or fumes, remove to fresh air. Get medical attention if

cough or other symptoms develop.

Ingestion Rinse mouth thoroughly with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Do not induce vomiting unless directed by

medical personnel. Get medical attention if symptoms occur.

Skin Contact Wash with soap and water. Get medical attention if irritation develops or persists.

Eye contact Rinse with water. Get medical attention if any discomfort continues.

5.Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Extinguish with the following media: Water spray, foam, dry powder or carbon dioxide.

Special hazards arising from the substance or mixture

Flammability Class No Uniform Fire Code noted.

Advice for firefighters

Protective actions during

firefighting

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

for firefighters

Special protective equipment Wear self-contained breathing apparatus as combustion may produce hazardous fumes.

6. Accidental release measures

Methods and material for containment and cleaning up

Methods for cleaning up

If dust is generated, use appropriate respiratory protection. Vacuum or sweep up material and place in a disposal container. Avoid generation and spreading of dust. Large Spillages: Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Avoid runoff into storm sewers and ditches which lead to waterways.

7. Handling and storage

Precautions for safe handling

Usage precautions

Minimize dust generation and accumulation. Do not breathe dust. Avoid contact with skin and eyes. Wash contaminated skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store dry at ambient temperature away from food and beverages, excessive heat or flame sources (furnace, kilns, boilers etc.). Store away from substances subject to catalytic decomposition by dust, e.g. peroxides

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

C.I. PIGMENT RED 101

Long-term exposure limit (8-hour TWA): OSHA 10 mg/m³ fume
Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction
Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³ respirable fraction

74

CRYSTALLINE SILICA

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m³ respirable fraction

A2

ALUMINUM OXIDE

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

CALCIUM OXIDE

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³

MAGNESIUM OXIDE

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ fume total particulate Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³ inhalable fraction

A4

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

A2 = Suspected Human Carcinogen.

Ingredient comments

Although no exposure limit has been established by OSHA for this product, the limit for nuisance particulates should be followed: OSHA 8-hr TWA 10mg/m3 Total Dust 5 mg/m3 respirable dust. ACGIH TLV-TWA 10mg/m3 Total dust or 5mg/m3 respirable dust.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Dusty powder.

Color Red-brown.

Odor Odorless.

Odor threshold Not available.

pH (diluted solution): 4-8 @10% suspension

Melting point > 1000°C/1832°F

Initial boiling point and range Not available.

Flash point Not available.

Evaporation rate Not available.

Evaporation factor Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or Not av

Not available.

explosive limits

Other flammability Not available.

Vapour pressure Not available.

Vapour density

Not available.

Relative density

Not available.

Bulk density

Not available.

Solubility(ies)

Insoluble in water.

Partition coefficient

Not available.

Auto-ignition temperature

Not available.

Decomposition Temperature

Not available.

Viscosity

Not available.

Explosive properties

Not available.

Volatile organic compound

None.

10. Stability and reactivity

Stability

No particular stability concerns.

Materials to avoid

Substances subject to catalytic decomposition caused by dust such as peroxides. Further avoid contact with aluminum dust, calcium hypochlorite, hydrazine, ethylene oxide, caesium

carbide.

11. Toxicological information

Information on toxicological effects

Toxicological effects

No specific toxicity tests have been carried out on this product.

Inhalation

Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin Contact

Substance may cause slight skin irritation.

Eye contact

May cause slight irritation.

12. Ecological Information

Ecotoxicity

The product is not expected to be hazardous to the environment.

Persistance and degradability

reisistence and degradable

Persistence and degradability The product is not readily biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential

Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient

Not available.

Mobility in soil

Mobility

The product is insoluble in water.

Other adverse effects

Other adverse effects

None known.

13. Disposal considerations

Waste treatment methods

General Information

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and

any local authority requirements.

14. Transport Information

General

This product is not covered by international regulation on the transport of dangerous goods

(IMDG, IATA, ADR/RID, DOT)

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

ALUMINUM OXIDE

1.0 %

MAGNESIUM OXIDE

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

CRYSTALLINE SILICA

None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

C.I. PIGMENT RED 101

Present.

ALUMINUM OXIDE

Present.

CALCIUM OXIDE

Present.

CRYSTALLINE SILICA

Present.

MAGNESIUM OXIDE

Present.

Rhode Island "Right To Know" List

C.I. PIGMENT RED 101

Present.

ALUMINUM OXIDE

Present.

CALCIUM OXIDE

Present.

CRYSTALLINE SILICA

Present.

MAGNESIUM OXIDE

Present.

Minnesota "Right To Know" List

C.I. PIGMENT RED 101

Present.

ALUMINUM OXIDE

Present.

CALCIUM OXIDE

Present.

CRYSTALLINE SILICA

Present.

MAGNESIUM OXIDE

Present.

New Jersey "Right To Know" List

C.I. PIGMENT RED 101

Present.

ALUMINUM OXIDE

Present.

CALCIUM OXIDE

Present.

CRYSTALLINE SILICA

Present.

MAGNESIUM OXIDE

Present.

Pennsylvania "Right To Know" List

C.I. PIGMENT RED 101

Present.

ALUMINUM OXIDE

Present.

CALCIUM OXIDE

Present.

CRYSTALLINE SILICA

Present.

MAGNESIUM OXIDE

Present.

Inventories

EU - EINECS/ELINCS

EINECS All the ingredients are listed or exempt.

Canada - DSL/NDSL

DSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

No.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

The following ingredients are not listed or exempt:

CRYSTALLINE SILICA

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date

6/3/2015

Revision

2

Supersedes date

3/24/2015

SDS No.

21020

SDS status

Approved.

Hazard statements in full

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs (Lungs) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.